

# NAI48-ES

## Network Audio Interface



Rear Panel




**Connect Yamaha digital mixing consoles or DME processors to remote head amps or AD/DA converters via EtherSound for analog interfacing wherever needed.**

- Transfer up to 48 channels of digital audio between console and stage or any other location via a single CAT5e Ethernet cable at sampling rates up to 96 kHz.
- Eliminates noise problems that are unavoidable with conventional analog gear and multi-cable type setups, and dramatically reduces analog cable length for superior sound quality.
- 48 AES/EBU inputs and 48 AES/EBU outputs are provided via 25-pin D-sub connectors.
- Designed with Yamaha professional sound gear in mind: minimum setup hassle, trouble-free operation.
- An external power supply can be used in addition to the internal power supply for redundant failsafe operation.
- Use standard Ethernet hubs and routers to create any network configuration you need.

### SYSTEM EXAMPLE

Live SR application using digital audio and AD8HR stagebox solution.



# NAI48-ES

## GENERAL SPECIFICATIONS

<b>Sampling Frequency</b>	42.9975kHz to 49.2kHz 85.995kHz to 98.4kHz
<b>Maximum I/O channel count</b>	48 IN/48 OUT (44.1/48kHz), 32 IN/32 OUT (88.2/96kHz)
<b>Power requirements</b>	AC100-240V 50/60Hz, and/or DC12V
<b>Power consumption</b>	12W
<b>Dimensions (W x H x D)</b>	480 x 44 x 150mm (18.9" x 1.73" x 5.9"), 1U
<b>Weight</b>	2.6kg (5.73lbs)

EtherSound™ is a trademark of Digigram.

## DIGITAL I/O SPECIFICATIONS

	Terminal	Format	Level	Connector
AES/EBU 1-6	IN	AES/EBU	RS422	D-sub 25P
	OUT			
EtherSound™	IN	100Base-TX	100Base-TX	RJ-45
	OUT			

## CONTROL I/O SPECIFICATIONS

	Terminal	Level	Connector
WORD CLOCK	IN	TTL/75Ω	BNC
	OUT		
HA Remote		RS422	D-sub 9P

## DIMENSIONS

